

THE NETHERLANDS



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning the:

- type-approval
- extension-of-type-approval
- refusal-of-type-approval
- withdrawal-of-type-approval

of a type of component (towing bracket) with regard to Directive 94/20/EC

Type-approval number: e4*94/20*0757*00

Reason for extension:

SECTION I

0.1	∐ake	(trade	name	of	manufacturer)) :	Eosal
-----	------	--------	------	----	---------------	-----	-------

0.2. Type and general commercial description(s) : 221791

0.3. Means of identification of type if

> marked on the component : Epproval number

0.3.1. Location of the marking : in type plate

0.5. Name and address of manufacturer : Eosal

> Fostbus 168 -920 AD MADE

0.7. In the case of components and separate technical units, location and method of

affixing of the EEC approval mark : on type plate

0.8. Name(s) and address(es) of assembly plants : see information

iocument

Annex III). item 0.8



SECTION II

 Additional information (where applicable)

: see Appendix I

2. Technical sevice responsible for

carrying out the tests

: RDW

Testbaan | Centrum Talingweg 76 8218 NX Lelystad

3. Date of test report : 21-05-1997


4. Number of test report : TCL-94/20-129/97

5. Remarks (if any) : see Appendix I

6. Place : Zoetermeer

7. Date :

8. Signature



- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request:
 - Application form relating to Annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Testreport, as mentioned in item 4.

Appendix I

to EEC type-approval certificate No : e4*94/20*0757*00 concerning the component type-approval of mechanical coupling devices with regard to Directive 94/20/EC

1. Additional information

1.1. Class of the type of coupling : A50-X

1.2. Categories or types of vehicles for which the device is designed

or restricted : see fitting instructions

1.3. Maximum D-value : 10.65 kN

1.4. Maximum vertical load S at the

coupling point : 90 kg

1.5. Maximum load U at the fifth wheel

coupling point : -- ton

1.6. Maximum V-value : -- kN

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fixing points at the vehicle given by the manufacturer; additional information if the use of the coupling type is restricted to

special types of vehicles : see fitting instructions

1.8. Information on the fitting of special towing brackets or

mounting plates : see fitting instructions

5. Remarks : The fitting of the towbar on the

vehicle must be checked according

to annex I, par.5.10,

according the prescriptions

mentioned in annex VII

