RDW



NEDERLAND (THE NETHERLANDS)



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning:

- type-approval
- extension of type-approval
- refusal of type-approval
- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number: e4*94/20*2575*00

Reason for extension:

SECTION I

Bosal 0.1. Make (trade name of manufacturer) Type and general commercial description(s) 033511 0.2. Means of identification of type marked on the : Type approval number 0.3. component On type plate 0.3.1. Location of that marking Name and address of manufacturer Bosal 0.5. Tweede industrieweg 6 4921 XH Made, the Netherlands In the case of components and separate technical: On type plate 0.7. units, location and method of affixing of the EEC type approval mark See information document Address(es) of assembly plant(s) 0.8.

(annex III, item 0.8)

Type-approval number: e4*94/20*2575*00

SECTION II

1. Additional information (where applicable)

See Appendix I

2. Technical service responsible for carrying out

the tests

RDW

Testbaan|Centrum

Talingweg 76

8218 NX Lelystad

3. Date of test report

: 10-08-2004

4. Number of test report

RDW-94/20-3861

5. Remarks (if any)

: See Appendix I

6. Place

: Zoetermeer

7. Date

: 10-08-2004

8. Signature

D.G. Burger

- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request.
 - Application form relating to annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Test report as mentioned in item 4.

Appendix I

to EEC type-approval certificate No: e4*94/20*2575*00 concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

1. Auditional illioimano.	1.	Additional	information
---------------------------	----	------------	-------------

1.1. Class of the type of coupling

: A50-X

1.2. Categories or types of vehicles for which the device is designed or restricted

See fitting instructions

1.3. Maximum D-value

: 8.91

kN

1.4. Maximum vertical load S at the coupling point:

75

kg

1.5 Maximum load U at the fifth wheel coupling point

: ----

ton

Maximum V-value

1.6.

kN

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle give by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles

: See fitting instructions



1.8 Information on the fitting of special towing brackets or mounting plates

: See fitting instructions

5. Remarks: The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par.5.10.