

THE NETHERLANDS



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning the:

- type-approval
- extension-of-type-approval
- refusal-of-type-approval
- withdrawal-of-type-approval

of a type of component (towing bracket) with regard to Directive 94/20/EC

Type-approval number: e4*94/20*0805*00

Reason for extension:

SECTION I

0.1 Make (trade name of manufacturer) : Le Rapide

0.2. Type and general commercial description(s) : 017096

0.3. Means of identification of type if

marked on the component : Approval number

0.3.1. Location of the marking : on type plate

0.5. Name and address of manufacturer : Bosal le Rapide

Avenue des Monts de Champagne 51490 BEINE NAUROY / FRANCE

0.7. In the case of components and separate technical units, location and method of

affixing of the EEC approval mark


0.8. Name(s) and address(es) of assembly plants

: on type plate

: see information

document

(Annex III), item 0.8



Type-approval number : e4*94/20*0805*00

SECTION II

1. Additional information (where applicable)

: see Appendix I

2. Technical sevice responsible for

carrying out the tests

: RDW

Testbaan|Centrum Talingweg 76

8218 NX Lelystad

3. Date of test report

4. Number of test report

: TCL-94/20-346/97

5. Remarks (if any)

: see Appendix I

: 03-07-1997

: Zoetermeer

6. Place

7. Date : 11. AUG 199

8. Signature



- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request:
 - Application form relating to Annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Testreport, as mentioned in item 4.

Appendix I to EEC type-approval certificate No : e4*94/20*0805*00 concerning the component type-approval of mechanical coupling devices with regard to Directive 94/20/EC

1. Additional information

coupling point

1.1. Class of the type of coupling : A50-X

1.2. Categories or types of vehicles for which the device is designed

or restricted : see fitting instructions

1.3. Maximum D-value : 7,43 kN

1.4. Maximum vertical load S at the coupling point : 52

1.5. Maximum load U at the fifth wheel

1.6. Maximum V-value : -- kN

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fixing points at the vehicle given by the manufacturer; additional information if the use of the coupling type is restricted to

special types of vehicles : see fitting instructions

1.8. Information on the fitting of special towing brackets or

mounting plates : see fitting instructions

5. Remarks : The fitting of the towbar on the

vehicle must be checked according annex I par.5.10, according the presciptions mentioned in annex

VΙΙ

kg

ton

